

SROT

SEONA Outer Type-SBFT Impeller



- Features

Impeller design is highly optimized to be driven either in water or in air.
 Can handle up to 100% solids of 100µm (0.1mm).


SEONA 100-150-200-300-500

Impeller shaft diameter is added to housing to allow for removal to maintain seals and the impeller can be changed without changing shaft.

SEONA Connecting to the Existing Motor/Generator

SEONA is a registered trademark of the company. All other trademarks are the property of their respective owners.

- Product Information

	Model	Specification
	Model 1	<ul style="list-style-type: none"> Capacity: 1000kg Power: 15kW
	Model 2	<ul style="list-style-type: none"> Capacity: 1500kg Power: 20kW
	Model 3	<ul style="list-style-type: none"> Capacity: 2000kg Power: 25kW
	Model 4	<ul style="list-style-type: none"> Capacity: 2500kg Power: 30kW
	Model 5	<ul style="list-style-type: none"> Capacity: 3000kg Power: 35kW
		

ASMETON S.p.A. - Via S. Maria Maddalena, 10 - 20139 Milano - Italy
 Tel: +39 02 575011 - Fax: +39 02 575012 - Email: info@asmeton.it

- Product Selection



Model 1	Capacity: 1000kg
Model 2	Capacity: 1500kg
Model 3	Capacity: 2000kg
Model 4	Capacity: 2500kg
Model 5	Capacity: 3000kg

ASMETON S.p.A. - Via S. Maria Maddalena, 10 - 20139 Milano - Italy
 Tel: +39 02 575011 - Fax: +39 02 575012 - Email: info@asmeton.it